

Tackwhite A 39 (V2)

Description

TACKWHITE A 39 is a water borne acrylic pressure sensitive adhesive. The product has a very high solid content and dries very fast. The dried film has a very aggressive initial tack and a good cohesion.

Application

TACKWHITE A 39 is suitable for the production of pressure sensitive packaging and office tapes on BOPP treated films. It is also suitable for other applications: label production, coating of foams, synthetic leathers and fabrics. If necessary, it can be formulated with resins, plasticizers, etc.

Packaging

The product is supplied in iron drums (200 kg); IBC containers (1000 kg).

Storing

For a safe storage of this emulsion, keep containers well sealed to prevent water evaporation and skin formation. The emulsion must be stored between 5°C and 40°C. Freezing must be avoided.

Use within 6 months from production date (unopened and in the original packaging).

Technical Specifications

Method of analysis	MU	Standard
1. Total Solids	%	56±2
3. Brookfield Viscosity 25°C	mPa.s	17,000 - 27,000
8. pH - Solvents	pH	7 - 9 water

Film properties

Method of analysis	MU	Standard
11. Peel Adhesion on Steel	g/in	600
17. Rolling Ball Tack	cm	4
22. Static Shear	h	> 100
97. Loop Tack Test	g	500

Average values; 22±2 g/m² of dry adhesive on PET film 36 µm