

## Tackwhite A 62 SF2

### Description

TACKWHITE A 62 SF2 is a pure acrylic p.s.a., in water dispersion, containing rosin esters. It is a permanent adhesive, that produces a very clear and transparent film, with an excellent light stability.

### Application

TACKWHITE A 62 SF2 is used mainly for permanent labels production (paper and plastic), double-sided tapes and foams.

### Technical Specifications

Method of analysis	MU	Standard
1. <b>Total Solids</b>	%	50±2
8. <b>pH</b>	pH	7 - 9
- <b>Solvents</b>		water
3. <b>Brookfield Viscosity</b> <b>25°C</b>	<b>mPa.s</b>	
TACKWHITE A 62 SF2		500 - 1,500 <sup>(1)</sup>
TACKWHITE A 62 SF2 (V2)		17,000 - 27,000 <sup>(2)</sup>

<sup>(1)</sup> N. 2 RV; 20 RPM

<sup>(2)</sup> No 6 RV; 20 RPM

### Film properties

Method of analysis	MU	Standard
11. <b>Peel Adhesion on Steel</b>	g/in	1,200 - 1,600
17. <b>Rolling Ball Tack</b>	cm	2 - 6
22. <b>Holding Power of</b> <b>Pressure Sensitive</b> <b>Tapes</b>	h	> 10

Average values; 22±2 g/m<sup>2</sup> of dry adhesive on PES film 23 µm

### Handling

The product can be applied using traditional coating systems: Meyer bar, air knife, rotogravure, ...

TACKWHITE A 62 SF2 is suitable for transfer coating, due to its good wettability on siliconed paper and film.

The coating weight depends on the final application, usually it goes from 20 to 40 g dry/sqm.

### Packing

TACKWHITE A 62 SF2 is supplied in 200 l drums or 1000 l tanks.

### Storing

TACKWHITE A 62 SF2 must be stored at temperature between +5°C and +40°C.

Shelf life is 3 months.